Blue Jacket Cable



Hazardous Environment Blue Jacket Cable

- ✓ Three 18 AWG Twisted Pairs
- ✓ Aluminium-Mytar tape, Aluminium side OUT
- ✓ 36 AWG tinned copper, 85% coverage
- ✓ .035" nominal wall of Blue PVC



SPECIFICATIONS

Blue Jacket Cable

Description:

Three 18 AWG Twisted Pairs, Overall Foil Shield, Braid Shield and PVC Jacket

Components

Three 18 AWG Twisted Pairs

Conductor: 18 AWG, 16/30 bare copper

Insulation: .016" nominal wall of PVC (see color code)

Pair: Two insulated conductors twisted together .144" (major axis)

6 Conductor polyurethane over 20 gauge wire Blue PVC Jacket 85% Braided Shield Foil Shield

Cable Construction

Cabling: Three twisted pairs cabled together

Foil Shield: Aluminum-Mylar tape, Aluminum side OUT

Braid: 36 AWG tinned copper, 85% coverage Jacket: .035" nominal wall of Blue PVC .366"

er(exposed run/filler)

Print

JMWC 3P 18 AWG SHIELDED 80C 900V

Color Code


Pair 1: Red, Black Pair 2: Green, White Pair 3: Blue, Brown

Requirements

Temperature: 80C Approvals: RoHS Compliant Voltage: 900V For intrinsically safe installation

per DIN EN 60079-14 and IEC 60079-14

TOTAL COMP LIMITED WARRANTY Total comp warrants this product to be free of defects in materials and/or workmanship and suitable for the purpose(s) intended as outlined on this sheet. This warranty is effective and shall cover the purchaser for one year from the date of shipment from our plant. If this product is found to be defective by our inspection in accordance with the above listed criteria, we will replace or repair it at our expense. For warranty service, please obtain a return authorization number from us and return the item, shipping prepaid, with a written description of the problem. We will respond promptly with the results of our evaluation.





99 Reagent Lane Fair Lawn, NJ 07410 Fax (201) 797-2287 Toll Free Fax (888) 797-2288 Phone (201) 797-2718 Toll Free Phone (800) 631-0347 Email sales@totalcomp.com Website www.totalcomp.com

6 Conductor polyurethane